

modbar®

ESPRESSO SYSTEM AV

The most consistent and stable under-counter espresso equipment available. Crafted and sold in full partnership with La Marzocco.



ESPRESSO SYSTEM AV



The product of years of collaborative R&D between Modbar and La Marzocco, and based on R&D from the Linea PB and Linea Mini, Modbar Espresso AV comes with the same level of reliability, performance and temperature stability that made the Linea PB an industry icon.

SPECIFICATIONS

- Linea PB volumetrics and optional scales
- multi-position lever with four saved programs
- add-a-tap system for two taps per module*
- easy access to water, power and drain connections
- pid temperature control
- simple heads-up display
- heads-up shot timer
- easy group access for maintenance
- heated brew group
- La Marzocco portafilters
- chromed tap

*only mod 2 gr

SPECS	TAP	MOD 2 GR	MOD 1 GR
Dimensions	5.5 x 12.5 x 14 in 14 x 32 x 36 cm	16 x 15 x 8.5 in 41 x 38 x 22 cm	16 x 15 x 8.5 in 41 x 38 x 22 cm
Weight	23 lbs 10.5 kg	40 lbs 18 kg	36.5 lbs 16,5 kg
Capacity		2.8 l dual boiler	1.4 l
ELECTRICAL	MOD 2 GR (CE)	MOD 2 GR (ETL)	MOD 1 GR
Voltage	208 - 240V	208 - 240V	208 - 240V / 110V
Amps	14A max ¹	14.2A max ¹	7A / 14A
Element Wattage	3227W max ¹	3264W max ¹	1520W
Frequency	50/60Hz	50/60Hz	50/60Hz
Phase	single	single	single
Certifications	CE	ETL ²	ETL ² , CE, NSF

¹ 1 mod + 2 taps

² listed for electrical safety in US and Canada, complies with UL-197 and CSA22.2 listed for sanitation, complies with NSF/ANSI Standard 4

modbar

www.modbar.com | @modbar

USA ☎ +1-260-454-5040 | 628 Leesburg Rd., Fort Wayne, IN, 46808

WORLD ☎ +39-055-849191 | Via La Torre 14/H, 50038, Scarperia e San Piero (FI), Italy