



## Necessary preparations before installing a 1-group La Marzocco coffee machine in Switzerland with fixed water connection

## **Attention:**

- Please do *not* plan the installation simultaneously with the plumber, electrician or carpenter: we only hook up to finished connections ready to plug in.
- Avoid installations during the construction phase to protect the machine.
- Tick all the boxes with the construction supervisor and inform us 48h before the installation if anything is not ready!
- Water must be running and all sockets powered!
- In case of unexpected delays, we will have to charge additional costs.

				$\checkmark$
Installation- compartment		Height = full counter height (800mm) Directly underneath the		
		Width = min. 400mm	machine for sockets ①, water	
		Depth = full counter depth (600mm)	in- ② and outlet ③, pump and water-filter	
Holo in	+abl	oton directly to the	Diameter (7 80 mm	
Hole in tabletop directly to the			Diameter Ø 80 mm	
installation compartment (for water pipes and cables)			Centered underneath the machine	
① Sockets		type 13 socket for coffee machine (1 x 230V/10A, P,N + E)  ug-in slot type 13 socket <u>per</u> grinder		
② Water inlet		a 3/8" or 1/8" fresh water line with stopcock.  d fresh water with at least 3 bar line pressure		
③ Water outlet	4	1x <mark>open</mark> syphon with at least 0 mm diameter and 150 mm riser		

## Visualization

